

TREBOR
BUILDING PRODUCTS LTD.


1499-B Star Top Road, Gloucester, Ontario K1B 3W5
 TEL.: (613) 749-6600 FAX: (613) 749-2790

TECHNICAL DATA SHEET

Z-BAR

Our Z-bar meet Canadian steel standards established by CSSBI (Canadian Institute of Sheet Steel Building).

They are available in five thicknesses: .018" - .034" - .045" - .056" and .068". They are manufactured only in lengths of 10'; see dimensions below:



DIMENSION A	DIMENSION B	DIMENSION C	THICKNESS
1 1/4" (31mm)	1"	1 1/4" (31mm)	.018" (.46mm) .034" (.86mm) .045" (1.14mm) .056" (1.42mm) .068" (1.7mm)
1 1/4" (31mm)	1 1/2"	1 1/4" (31mm)	
1 1/4" (31mm)	2"	1 1/4" (31mm)	
1 1/4" (31mm)	2 1/2"	1 1/4" (31mm)	
1 1/4" (31mm)	3"	1 1/4" (31mm)	
1 1/4" (31mm)	3 1/2"	1 1/4" (31mm)	
1 1/4" (31mm)	4"	1 1/4" (31mm)	
1 1/4" (31mm)	4 1/2"	1 1/4" (31mm)	
1 1/4" (31mm)	5"	1 1/4" (31mm)	
1 1/4" (31mm)	5 1/2"	1 1/4" (31mm)	
1 1/4" (31mm)	6"	1 1/4" (31mm)	

Z-bar is made to hold different thicknesses of rigid insulation. It can be used for interior or exterior applications.

Galvanizing used for the components is described in the CSSBI Technical Bulletin of February 2006, G60 (Z-180) for all thicknesses.

